

FBV-3-Press Ball Valve

for Water Service

Sizes: 2½" – 4" (65 – 100mm)

Installation Instructions

The FBV-3-Press ball valve is designed for use with types K, L and M Hard Copper Tubing in 2½" – 4" (65 – 100mm)

Warning: Please read and understand the following instructions for installing FBV-3-Press ball valves. Failure to follow all instructions may result in extensive property damage or serious injury.

1. Square cut copper tubing at right angle, using a Displacement type cutter.
2. To prevent cutting the O-ring, carefully deburr the internal and external surface of the tube end.
3. Mark the correct insertion depth on the tube. Refer to FBV-3-Press Insertion Depth Chart below for insertion depth. Incorrect insertion depth can result in failed press connection.
4. The tubing is now ready to insert in the ball valve. Do not use oil or lubricant on the valve fitting or tube. This will degrade the FBV-3-Press EPDM.
5. Slowly rotate the valve while sliding the valve on the tubing. Insert to depth marked on tube.
6. Place XL ring at right angle to the FBV-3-Press ball valve fitting. Place XL ring on the fitting bead. Check insertion depth mark on the tubing before pressing.
7. Assemble pressing tool to the manufacturer's recommendation.
8. To start the press connection process, place the actuator into the XL ring. Press the trigger until the actuator has completed the press joint. Be careful to keep extremities and other objects away from the actuator or XL ring during the pressing as injury or failed press joint can occur.
9. Remove the XL ring from the ball valve fitting when the press connection is completed.
10. Pressure testing to be performed in accordance with the local codes and fitting manufacturer's instructions.

FBV-3-Press Insertion Depth Chart

Tube Size	2½" 65mm	3" 80mm	4" 100mm
Insertion Depth	2⅛" 54mm	2⅓" 54mm	2½" 65mm

CALIFORNIA PROPOSITION 65 WARNING

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. (California law requires this warning to be given to customers in the State of California.)

For more information: www.watts.com/prop65

Limited Warranty: Watts Regulator Co. (the "Company") warrants each product to be free from defects in material and workmanship under normal usage for a period of one year from the date of original shipment. In the event of such defects within the warranty period, the Company will, at its option, replace or recondition the product without charge.

THE WARRANTY SET FORTH HEREIN IS GIVEN EXPRESSLY AND IS THE ONLY WARRANTY GIVEN BY THE COMPANY WITH RESPECT TO THE PRODUCT. THE COMPANY MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. THE COMPANY HEREBY SPECIFICALLY DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The remedy described in the first paragraph of this warranty shall constitute the sole and exclusive remedy for breach of warranty, and the Company shall not be responsible for any incidental, special or consequential damages, including without limitation, lost profits or the cost of repairing or replacing other property which is damaged if this product does not work properly, other costs resulting from labor charges, delays, vandalism, negligence, fouling caused by foreign material, damage from adverse water conditions, chemical, or any other circumstances over which the Company has no control. This warranty shall be invalidated by any abuse, misuse, misapplication, improper installation or improper maintenance or alteration of the product.

Some States do not allow limitations on how long an implied warranty lasts, and some States do not allow the exclusion or limitation of incidental or consequential damages. Therefore the above limitations may not apply to you. This Limited Warranty gives you specific legal rights, and you may have other rights that vary from State to State. You should consult applicable state laws to determine your rights. **SO FAR AS IS CONSISTENT WITH APPLICABLE STATE LAW, ANY IMPLIED WARRANTIES THAT MAY NOT BE DISCLAIMED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED IN DURATION TO ONE YEAR FROM THE DATE OF ORIGINAL SHIPMENT.**



Water Safety & Flow Control Products

ISO 9001-2000
CERTIFIED

