


Tag: \_\_\_\_\_


**SPECIFICATION:** BLÜCHER PIPE AISI Type 316L (standard) stainless steel pipe system, with Push-Fit socket connections with EPDM (standard) sealing ring. All BLÜCHER PIPE to be treated with pickling and passivation finish process.

### Bulkhead Penetration with Welding Sleeve




| Model No. 316L / Global Part # | D        | D2            | X             | X5            | X6     | T        |
|--------------------------------|----------|---------------|---------------|---------------|--------|----------|
| 866.025.040.10FS               | 1.5"(40) | 2"(50)        | 9-13/16"(250) | 3-15/16"(100) | 3"(75) | 3/16"(5) |
| 866.025.050.10FS               | 2"(50)   | 2-3/8"(60)    | 9-13/16"(250) | 3-15/16"(100) | 3"(75) | 3/16"(5) |
| 866.025.075.10FS               | 3"(75)   | 3-3/8"(85)    | 9-13/16"(250) | 3-15/16"(100) | 3"(75) | 3/16"(5) |
| 866.025.110.10FS               | 4"(110)  | 4-3/4"(120)   | 9-13/16"(250) | 3-15/16"(100) | 3"(75) | 3/16"(5) |
| 866.025.160.10FS               | 6"(160)  | 6-11/16"(170) | 9-13/16"(250) | 3-15/16"(100) | 3"(75) | 3/16"(5) |

### Wash Basin Penetration with Welding Sleeve




| Model No. 316L / Global Part # | D          | D1     | H             | D2         | X5         | X6     | T        |
|--------------------------------|------------|--------|---------------|------------|------------|--------|----------|
| 866.032.050.05S                | 1-1/4"(32) | 2"(50) | 6-13/16"(173) | 2-3/8"(60) | 2-1/4"(57) | 2"(50) | 3/16"(5) |

### Toilet Penetration for Vacuum System with Welding Sleeve




| Model No. 316L / Global Part # | D        | H           | D2         | X5     | X6            | T        |
|--------------------------------|----------|-------------|------------|--------|---------------|----------|
| 867.020.040.10S                | 1.5"(40) | 7-7/8"(200) | 2"(50)     | 2"(50) | 3-15/16"(100) | 3/16"(5) |
| 867.020.050.10S                | 2"(50)   | 7-7/8"(200) | 2-3/8"(60) | 2"(50) | 3-15/16"(100) | 3/16"(5) |

### Deck Penetration with Welding Flange



| Model No. 316L / Global Part # | D        | H           | D2            | X           | T        |
|--------------------------------|----------|-------------|---------------|-------------|----------|
| 868.100.040FS                  | 1.5"(40) | 6"(152)     | 3-9/16"(90)   | 2-3/16"(55) | 3/16"(5) |
| 868.105.050FS                  | 2"(50)   | 6-1/4"(159) | 3-15/16"(100) | 2-1/4"(57)  | 3/16"(5) |
| 868.115.075FS                  | 3"(75)   | 6-7/8"(175) | 5-5/16"(135)  | 2-7/16"(62) | 3/16"(5) |
| 868.125.110FS                  | 4"(110)  | 7-7/8"(200) | 6-5/16"(160)  | 3-1/8"(79)  | 3/16"(5) |

### Socket Deck Penetration with Welding Sleeve



| Model No. 316L / Global Part # | D        | H             | D2          | X5            | T        |
|--------------------------------|----------|---------------|-------------|---------------|----------|
| 870.000.040FS                  | 1.5"(40) | 5-15/16"(151) | 3-9/16"(90) | 3-15/16"(100) | 3/16"(5) |
| 870.000.050FS                  | 2"(50)   | 6-1/8"(155)   | 3-9/16"(90) | 3-15/16"(100) | 3/16"(5) |
| 870.000.075FS                  | 3"(75)   | 6-9/16"(167)  | 4-1/4"(108) | 3-15/16"(100) | 3/16"(5) |
| 870.000.110FS                  | 4"(110)  | 6-9/16"(167)  | 5-1/2"(140) | 3-15/16"(100) | 3/16"(5) |

Job Name \_\_\_\_\_ Contractor \_\_\_\_\_


Job Location \_\_\_\_\_ Approval \_\_\_\_\_

Engineer \_\_\_\_\_ Contractor's P.O. No. \_\_\_\_\_

Approval \_\_\_\_\_ Representative \_\_\_\_\_


**SPECIFICATION:** BLÜCHER PIPE AISI Type 316L (standard) stainless steel pipe system, with Push-Fit socket connections with EPDM (standard) sealing ring. All BLÜCHER PIPE to be treated with pickling and passivation finish process.

## Deck Penetration with Welding Sleeve



| Model No. 316L /<br>Global Part # | D        | H             | D2          | X5            | T        |
|-----------------------------------|----------|---------------|-------------|---------------|----------|
| 872.050.040S                      | 1.5"(40) | 5-15/16"(150) | 2"(50)      | 3-15/16"(100) | 3/16"(5) |
| 872.060.050S                      | 2"(50)   | 6-1/8"(155)   | 2-3/8"(60)  | 3-15/16"(100) | 3/16"(5) |
| 872.076.075S                      | 3"(75)   | 6-5/16"(160)  | 3"(76)      | 3-15/16"(100) | 3/16"(5) |
| 872.089.075S                      | 3"(75)   | 6-5/16"(160)  | 3-1/2"(89)  | 3-15/16"(100) | 3/16"(5) |
| 872.114.110S                      | 4"(110)  | 6-1/8"(155)   | 4-1/2"(114) | 3-15/16"(100) | 3/16"(5) |

## Aluminum Deck Penetration with Bi-Metal Welding Flange



| Model No. 316L /<br>Global Part # | D       | H            | D2            | D3           | X           | T       | T1       |
|-----------------------------------|---------|--------------|---------------|--------------|-------------|---------|----------|
| 878.105.050S                      | 2"(50)  | 6-9/16"(166) | 3-7/16"(88)   | 4-3/16"(110) | 2-1/4"(57)  | 1/4"(6) | 3/16"(4) |
| 878.115.075S                      | 3"(75)  | 7-3/16"(182) | 4-7/16"(113)  | 5-5/16"(136) | 2-7/16"(62) | 1/4"(6) | 3/16"(4) |
| 878.125.110S                      | 4"(110) | 8-1/8"(207)  | 5-13/16"(148) | 6-3/4"(172)  | 3-1/8"(79)  | 1/4"(6) | 3/16"(4) |