For Commercial and Residential Applications

Job Name _____ Contractor _____

Job Location _____ Approval _____

Engineer _____ Contractor's P.O. No. _____

Approval _____ Representative _____

Series CTC-P

Flexible Reinforced PVC Water Supply Connectors for Toilets

Sizes: ⅜" to ⅞" (10 to 22mm)

Series CTC-P Flexible Reinforced PVC Water Supply Connectors for Toilets are used in residential and commercial applications, specifically for hookups to a toilet water supply. These connectors provide protection from vibration and bursting under extreme pressure surges. Series CTC-P connectors consist of white flexible PVC tubing jacketed with braided nylon, an outer protective layer of PVC, and permanently attached, brass, compression end fitting and glass-reinforced polypropylene ballcock nut. Various end connections are available.

CTC-P

Features

- Available in lengths: 6", 9", 12", 16", and 20" (150, 230, 300, 400, 500mm)
- Tubing
  - PVC body
  - Braided nylon jacket
- Protective PVC outer layer
- Brass compression end fittings
- Glass-reinforced polypropylene ballcock nut

Standards

UPC Listed

Pressure-Temperature

Maximum Working Pressure: 125psi (8.6 bar)

Maximum Temperature: 140°F (60°C)

Note: National residential plumbing codes reference the maximum operating temperature as 140°F (60°C). Plumbing fixtures are designed to ANSI—ASME A112 18.1 at 1125psi.

Models

CTC-P-CB One end of the flexible connector is supplied with ballcock polypropylene nut. The other end is supplied with a plated, solid brass compression end fitting for connection to a supply stop valve.

CTC-P-FB One end of the flexible connector is supplied with a ballcock polypropylene nut. The other end is supplied with a plated, solid brass female iron pipe thread fitting.

CTC-P-TB One end of the flexible connector is supplied with a ballcock polypropylene nut. The other end is supplied with a solid brass fine thread female iron pipe fitting.

Materials

Tubing:

Body: PVC

Jacket: Nylon

Protective Layer: PVC

Fittings: Brass

Glass-reinforced polypropylene

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

WATTS®

Dimensions

PRODUCT NO.	INDIVIDUAL SIZE	WGT. (LBS.)
CTC-P-CB	3/8" x 7/8" x 6"	0.08
CTC-P-CB	3/8" x 7/8" x 9"	0.10
CTC-P-CB	3/8" x 7/8" x 12"	0.12
CTC-P-CB	3/8" x 7/8" x 16"	0.16
CTC-P-CB	3/8" x 7/8" x 20"	0.20
CTC-P-CB	3/8" x 7/8" x 30"	0.30
CTC-P-CB	7/16" x 7/8" x 6"	0.08
CTC-P-CB	7/16" x 7/8" x 9"	0.10
CTC-P-CB	7/16" x 7/8" x 12"	0.12
CTC-P-CB	7/16" x 7/8" x 16"	0.16
CTC-P-CB	7/16" x 7/8" x 20"	0.20
CTC-P-CB	7/16" x 7/8" x 30"	0.80
CTC-P-CB	1/2" x 7/8" x 6"	0.08
CTC-P-CB	1/2" x 7/8" x 9"	0.10
CTC-P-CB	1/2" x 7/8" x 12"	0.12
CTC-P-CB	1/2" x 7/8" x 16"	0.16
CTC-P-CB	1/2" x 7/8" x 20"	0.20
CTC-P-CB	1/2" x 7/8" x 30"	0.30
CTC-P-FB	1/2" x 7/8" x 6"	0.08
CTC-P-FB	1/2" x 7/8" x 9"	0.10
CTC-P-FB	1/2" x 7/8" x 12"	0.12
CTC-P-FB	1/2" x 7/8" x 16"	0.16
CTC-P-FB	1/2" x 7/8" x 20"	0.20
CTC-P-TB	3/8" x 7/8" x 6"	0.08
CTC-P-TB	3/8" x 7/8" x 9"	0.10
CTC-P-TB	3/8" x 7/8" x 12"	0.12
CTC-P-TB	3/8" x 7/8" x 16"	0.16
CTC-P-TB	3/8" x 7/8" x 20"	0.20
CTC-P-TB	3/8" x 7/8" x 30"	0.30
CTC-P-TB	1/2" x 7/8" x 6"	0.08
CTC-P-TB	1/2" x 7/8" x 9"	0.10
CTC-P-TB	1/2" x 7/8" x 12"	0.12
CTC-P-TB	1/2" x 7/8" x 16"	0.16
CTC-P-TB	1/2" x 7/8" x 20"	0.20

© 2012 Watts