

For Commercial and Residential Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Series CWM-A

Flexible Connectors with Microban® Antimicrobial Technology Water Supply for Washing Machines

Size: 3/4" (20mm)

Series CWM-A Flexible Braided PVC Connectors for Washing Machines are used in residential and commercial applications, specifically for washing machine hookups. These connectors provide full flow capacity and protection from vibration and bursting under pressure surges caused by washing machine solenoid valves. Series CWM-A connectors consist of white flexible PVC tubing jacketed with braided nylon polyester yarn and an outer protective layer of PVC with infused Microban® antimicrobial technology to inhibit the growth of bacteria that can cause stains, odors and product degradation.

Features

- Available in lengths: 48", 60", and 72" (1200, 1500, or 1800mm)
- Tubing
 - PVC body jacket
 - Braided with polyester yarn
 - Protective PVC outer layer with Microban®
 - Composite nuts
- Convenient for difficult installations
- Electrically non-conductive between connection points and on the hose surface to prevent grounding, sparks and electronic interference to and from other devices.
- No tube cutting or bending
- No soldering
- No extra adapters, fittings or couplings required
- No tools

Standards

UPC Listed



Pressure-Temperature

Maximum Working Pressure: 125psi (8.6 bar)

Maximum Temperature: 140°F (60°C)

Note: National residential plumbing codes reference the maximum operating temperature as 140°F (60°C). Plumbing fixtures are designed to ANSI—ASME A112 18.1 at 125psi.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

ISO 9001-2008
CERTIFIED



USA: Tel: (978) 688-1811 • Fax: (978) 794-1848 • www.watts.com
Canada: Tel: (905) 332-4090 • Fax: (905) 332-7068 • www.watts.ca

ES-CWM-A 1225



CWM-A-HH

Models

CWM-A-HH - Supplied with standard composite female hose thread fittings at each end of the flexible connector.

Materials

Tubing:

Body: PVC

Jacket: Braided with polyester yarn

Protective Layer: PVC - with Antimicrobial Technology

Fittings: Composite nuts

Washer: EPDM

Dimensions

MODEL	SIZE	UNIT WGT. (LBS.)
CWM-A-HH	3/4" x 3/4" x 48"	0.5
CWM-A-HH	3/4" x 3/4" x 60"	0.8
CWM-A-HH	3/4" x 3/4" x 72"	1.1

The Microban® trademark and all related trademarks are the trademarks, service marks or registered trademarks of Microban International, Ltd. and its subsidiaries.

WATTS®

A Watts Water Technologies Company

© 2012 Watts