

For Commercial and Residential Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

LEAD FREE*

Series LFCFC-A

Flexible Connectors with Microban® Antimicrobial Technology Water Supply for Faucets

Sizes: 3/8" to 1/2" (10 to 15mm)

Series LFCFC-A Flexible Reinforced PVC Water Supply Connectors for Faucets with Microban® Antimicrobial Technology are used in residential and commercial applications, specifically for hookups to the faucet water supply. These connectors offer protection from vibration and bursting under extreme pressure surges. Series LFCFC-A connectors consist of white flexible PVC tubing jacketed with braided nylon polyester yarn and an outer protective layer of PVC with infused Microban® antimicrobial technology to inhibit the growth of bacteria that can cause stains, odors and product degradation.

Features

- Available in lengths: 12", 16", 20" (300, 400, 500mm)
- Tubing
 - PVC body jacket
 - Braided with polyester yarn
 - Protective PVC outer layer with Microban®
 - Composite nuts
- Convenient for difficult installations
- No tube cutting or bending
- No soldering
- No extra adapters, fittings or couplings required
- No tools

Standards

NSF and UPC Listed



Pressure-Temperature

Maximum Working Pressure: 125psi (8.6 bar)

Maximum Temperature: 140°F (60°C)

Note: National residential plumbing codes reference the maximum operating temperature as 140°F (60°C). Plumbing fixtures are designed to ANSI—ASME A112.18.1 at 125psi.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

ISO 9001-2008
CERTIFIED



USA: Tel: (978) 688-1811 • Fax: (978) 794-1848 • www.watts.com
Canada: Tel: (905) 332-4090 • Fax: (905) 332-7068 • www.watts.ca

ES-LFCFC-A 1225



LFCFC-A-CF

Models

CFC-A-CF One end of the flexible connector is supplied with a composite compression end fitting for connection to a supply stop valve. The other end is supplied with a composite female iron pipe thread fitting.

Materials

Tubing:

Body: PVC

Jacket: Braided with polyester yarn

Protective Layer: PVC - with Antimicrobial Technology

Fittings: Composite nuts

Washer: EPDM

Dimensions

	MODEL	SIZE	UNIT WGT. (LBS.)
LEAD FREE	LFCFC-A-CF	3/8" x 1/2" x 12"	0.16
	LFCFC-A-CF	3/8" x 1/2" x 16"	0.16
	LFCFC-A-CF	3/8" x 1/2" x 20"	0.20

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

The Microban® trademark and all related trademarks are the trademarks, service marks or registered trademarks of Microban International, Ltd. and its subsidiaries.

WATTS®

A Watts Water Technologies Company

© 2012 Watts