

# Model: 1011G

## LOCXEND® Suction Diffusers Sizes: 2" x 1¼" – 12" x 12" (50 x 32 – 300 x 300mm)

Pressure / Temperature – Non-Shock	
Model	CWP
1011G	300psi @ 100°F 165psi @ 300°F

Max. temp can be limited by O-ring material.



Model 1011G

Mueller Steam Specialty LOCXEND® Suction Diffusers provide economical and compact pump protection by straining foreign particles and providing proper flow conditions to the pump.

### Typical Service

- Mount directly to the suction side of a pump, in either horizontal or vertical position.

### Features

- Compact design enables this one unit to act as an elbow, strainer, and entry pipe to the suction side of the pump. This reduces installation time, overall cost, and reduces joint leak paths.
- Equal size flanges or reduced outlet flange sizes available. Reduced outlet design eliminates the need for a reducing base elbow.
- Quick opening knobs allow for quick maintenance.
- O-ring seal eliminates the need to clean the sealing area and install a new flat gasket in competitive models.
- Straightening vanes on the Suction Diffuser's outlet side reduces turbulence into the pump. These minimize stress and erosion within the pump, and eliminate the need for a length of straight pipe to diminish turbulence.
- Robust 5 to 1 Open Area Ratio and blow off feature extend the time between servicing and allows for ease of draining and flushing
- A separate removable fine mesh screen liner is installed in each Diffuser for start-up. After the start-up period, simply remove and discard, leaving the primary screen for operation.
- Special pads fit the I.D. of standard pipe, eliminating the need for pipe saddles and relieving stress on hanger systems.
- Gauge tapping in available as specified with the order.

### Screens

MODEL	SIZES	STANDARD (WATER)	
		MATERIAL	OPENING
1011	Up to 6"	304SS	.156 perf
1011	8" and Up	304SS	.125 perf
Sleeve		304SS	20 mesh

Job Name \_\_\_\_\_

Contractor \_\_\_\_\_

Job Location \_\_\_\_\_

Approval \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor's P.O. No. \_\_\_\_\_

Approval \_\_\_\_\_

Representative \_\_\_\_\_


## Materials

1011	
Body and Cover	Cast Iron ASTM A126-B
Knobs	(2" x 1¼" - 8" x 8") – Ductile Iron ASTM A536
Nuts:	(10" x 10" and larger) – Carbon Steel ASTM A194-4
Sleeve:	20 mesh Stainless Steel
O-Ring:	EPDM

Special metals and alloys on request.

Models with flanged inlet available in Cast Iron for Class 125 and Ductile Iron for Class 300 service.

## Dimensions and Weights



Model 1011G

SIZE		DIMENSIONS														WEIGHT			
in.	mm	A		B		C		D		E		F Screen Removal		G		H Pipe Support I.D.		lbs.	kgs.
		in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm				
2 x 1¼	51 x 32	On Application	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
2 x 1½	51 x 38	On Application	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
2 x 2	51 x 51	4½	114	4½	114	6 <sup>11</sup> / <sub>16</sub>	170	6 <sup>1</sup> / <sub>8</sub>	156	10 <sup>9</sup> / <sub>16</sub>	259	8 <sup>13</sup> / <sub>16</sub>	224	¾ NPT	20	.824	21	19	42
2½ x 2	64 x 51	5	127	5	127	7½	191	6 <sup>9</sup> / <sub>16</sub>	167	10 <sup>7</sup> / <sub>8</sub>	276	9 <sup>1</sup> / <sub>8</sub>	232	¾ NPT	20	1.380	35	20	44
2½ x 2½	64 x 64	5	127	5	127	7½	191	6 <sup>9</sup> / <sub>16</sub>	167	10 <sup>7</sup> / <sub>8</sub>	276	9 <sup>1</sup> / <sub>8</sub>	232	¾ NPT	20	1.380	35	22	49
3 x 2	76 x 51	5½	140	5½	140	8 <sup>7</sup> / <sub>16</sub>	189	7 <sup>7</sup> / <sub>8</sub>	187	11 <sup>1</sup> / <sub>16</sub>	294	9 <sup>5</sup> / <sub>8</sub>	244	¾ NPT	20	1.380	35	38	84
3 x 2½	76 x 64	5½	140	5½	140	8 <sup>7</sup> / <sub>16</sub>	189	7 <sup>7</sup> / <sub>8</sub>	187	11 <sup>1</sup> / <sub>16</sub>	294	9 <sup>5</sup> / <sub>8</sub>	244	¾ NPT	20	1.380	35	39	86
3 x 3	76 x 76	5½	140	5½	140	8 <sup>7</sup> / <sub>16</sub>	189	7 <sup>7</sup> / <sub>8</sub>	187	11 <sup>1</sup> / <sub>16</sub>	294	9 <sup>5</sup> / <sub>8</sub>	244	¾ NPT	20	1.380	35	40	88
4 x 3	102 x 76	6½	165	6 <sup>19</sup> / <sub>16</sub>	173	10 <sup>7</sup> / <sub>16</sub>	265	8 <sup>3</sup> / <sub>4</sub>	223	13 <sup>3</sup> / <sub>8</sub>	333	11½	292	1 NPT	25	1.380	35	50	110
4 x 4	102 x 102	6½	165	6 <sup>19</sup> / <sub>16</sub>	173	10 <sup>7</sup> / <sub>16</sub>	265	8 <sup>3</sup> / <sub>4</sub>	223	13 <sup>3</sup> / <sub>8</sub>	333	11½	292	1 NPT	25	1.380	35	52	115
6 x 4	152 x 102	8	203	8	203	13 <sup>9</sup> / <sub>16</sub>	338	10½	267	16 <sup>7</sup> / <sub>8</sub>	429	16 <sup>9</sup> / <sub>16</sub>	421	1 NPT	25	1.380	35	106	234
6 x 5	152 x 127	8	203	8	203	13 <sup>9</sup> / <sub>16</sub>	338	10½	267	16 <sup>7</sup> / <sub>8</sub>	429	16 <sup>9</sup> / <sub>16</sub>	421	1 NPT	25	1.380	35	110	242
6 x 6	152 x 152	8	203	8	203	13 <sup>9</sup> / <sub>16</sub>	338	10½	267	16 <sup>7</sup> / <sub>8</sub>	429	16 <sup>9</sup> / <sub>16</sub>	421	1 NPT	25	1.380	35	113	249
8 x 6	203 x 152	9	229	10	254	15 <sup>9</sup> / <sub>16</sub>	389	11½	292	17 <sup>7</sup> / <sub>8</sub>	454	16 <sup>7</sup> / <sub>8</sub>	429	1 NPT	25	1.380	35	137	302
8 x 8	203 x 203	9	229	10	254	16 <sup>5</sup> / <sub>16</sub>	414	11¾	298	20 <sup>3</sup> / <sub>4</sub>	527	22 <sup>7</sup> / <sub>8</sub>	581	1¼ NPT	32	1.380	35	222	490
10 x 8	254 x 203	9	229	11¾	298	18 <sup>7</sup> / <sub>16</sub>	468	11¾	298	20 <sup>3</sup> / <sub>4</sub>	527	22 <sup>7</sup> / <sub>8</sub>	581	1¼ NPT	32	1.380	35	236	520
10 x 10	254 x 254	11	280	11¾	298	20	508	14	356	26 <sup>3</sup> / <sub>8</sub>	670	30¾	781	1¼ NPT	32	1.380	35	343	756
12 x 8	305 x 203	On Application	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
12 x 10	305 x 254	11	280	12 <sup>7</sup> / <sub>8</sub>	327	21	533	14	356	26 <sup>3</sup> / <sub>8</sub>	670	30¾	781	1¼ NPT	32	1.380	35	357	787
12 x 12	305 x 305	On Application	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

Mueller Steam Specialty product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Mueller Steam Specialty Technical Service. Mueller Steam Specialty reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Mueller Steam Specialty products previously or subsequently sold.



A Watts Water Technologies Company

USA: St. Pauls, NC • Tel. 1-800-334-6259 • Fax 1-800-421-6772 • www.muellersteam.com

ES-MS-1011G 1020



ISO 9001-2008  
CERTIFIED

© 2010 Mueller Steam Specialty