

**Model: 352½MM****Cast Bronze Sil-Braze Ends Y Strainers**  
**Sizes: ¼" - 4" (8 - 100mm)****Pressure/Temperature - Non-Shock**

Model	Material	Rating
352½	Bronze	250psi @ 425°F 17.2 bar @ 218°C

**352½M Sil-Braze Class 125**

352½MM Sil-Braze ends

**Typical Service**

- Used to strain foreign matter from pipelines and provide economical protection for costly pumps, meters, valves, and other similar mechanical equipment

**Features**

- Machined seats in both body and cap align and lock the screen in place to stop sediment bypass.
- 352-½ conforms to Military specifications
- 352-½ conforms to the latest revision of BuShip Drawing 80064-810-841499.
- All sizes of 352-½ are furnished grooved less rings.

**Self-Cleaning**

- Self-cleaning is accomplished by opening the plug or valve connected to the blowoff outlet

**Blowoff Outlets**

- Outlets are NPT tapped
- Sizes of tapping are specified on next page
- Not normally furnished with plug. Plug is available, specify with order.
- BuShip Drawing strainers are supplied without blowoff outlets.

**Capacity**

- Generously proportioned bodies
- Open Area Ratio much greater than pipe size, ensuring low pressure drop.

**Screens**

MODEL	SIZES	STANDARD (WATER)		STEAM RECOMENDATION	
		MATERIAL	OPENING	MATERIAL	OPENING
352-1/2M	¼" - 2"	304SS	20 mesh	304SS	.033 perf
352-1/2M	2½" - 4"	304SS	.062 perf	304SS	.033 perf

**Materials**

	352½MM
Body	Bronze ASTM B61
Cap	Bronze ASTM B61
Screen	304SS
Gasket	Copper

Job Name \_\_\_\_\_

Contractor \_\_\_\_\_

Job Location \_\_\_\_\_

Approval \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor's P.O. No. \_\_\_\_\_

Approval \_\_\_\_\_


Representative \_\_\_\_\_

## Pressure Drop

See Pressure Drop Charts in Technical Data Section of the Mueller Steam Specialty Engineering binder.

## Dimensions and Weights

SIZE		DIMENSIONS						WEIGHT			
		A		B		C (NPT)		D Screen Removal			
in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kgs.
<b>352½MM</b>											
¼	8	2 <sup>9</sup> / <sub>16</sub>	65	1 <sup>1</sup> / <sub>8</sub>	48	¼	3	2 <sup>3</sup> / <sub>4</sub>	70	.75	.34
⅜	10	2 <sup>9</sup> / <sub>16</sub>	65	1 <sup>1</sup> / <sub>8</sub>	48	¼	3	2 <sup>3</sup> / <sub>4</sub>	70	.75	.34
½	15	2 <sup>15</sup> / <sub>16</sub>	75	2 <sup>1</sup> / <sub>8</sub>	54	¼	3	3	76	1	.45
¾	20	3 <sup>3</sup> / <sub>8</sub>	86	2 <sup>9</sup> / <sub>16</sub>	65	¼	6	4	102	1.75	.79
1	25	4 <sup>1</sup> / <sub>8</sub>	105	3 <sup>1</sup> / <sub>8</sub>	79	¼	6	4½	114	2.5	1.1
1¼	32	4 <sup>13</sup> / <sub>16</sub>	122	3 <sup>3</sup> / <sub>8</sub>	90	¾	10	5½	140	4.25	1.9
1½	40	5 <sup>3</sup> / <sub>8</sub>	137	4 <sup>3</sup> / <sub>16</sub>	122	½	15	6½	165	5.5	2.5
2	50	6 <sup>3</sup> / <sub>8</sub>	168	5 <sup>3</sup> / <sub>8</sub>	137	¾	20	8¼	210	8.25	3.7
2½	65	7 <sup>7</sup> / <sub>8</sub>	200	6½	165	1	25	10	254	15.5	7
3	80	11¾	298	7	178	1	25	10½	267	36	16
4	100	15¾	386	11¾	289	Blind Cover		16	406	90	41



Mueller Steam Specialty product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Mueller Steam Specialty Technical Service. Mueller Steam Specialty reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Mueller Steam Specialty products previously or subsequently sold.



A Watts Water Technologies Company

USA: Tel: (800) 334-6259 • Fax: (800) 421-6772 • MuellerSteam.com  
 Latin America: Tel: (52) 81-1001-8600 • Fax: (52) 81-8000-7091 • MuellerSteam.com

ES-MS-352-1\_2MM 1453

© 2014 Mueller Steam Specialty