

For Non-Health Hazard Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____


Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

LEAD FREE*
HydroGuard® Master
Tempering Valve Supply
Fixture
Series LFLM490 Bottom Inlets/Top
Outlet — Wall Mounted Cabinet



Features

- Features Lead Free* construction to comply with Lead Free* installation requirements.
- Paraffin-based advanced thermal actuation technology to sense and adjust outlet temperature
- Dirt and lime resistant poppet and seat design
- Virtual shutoff if supply pressure fails
- Stainless steel or white painted cabinets
- Factory tested valve and piping
- Triple-duty checkstops with filters, dial-thermometer, ball valve
- Rough bronze and chrome finishes



Advanced Thermal Activation

Specifications

Connections ½" (15mm) inlets and outlet
 Maximum Hot Water Supply Temperature 200°F (93°C)
 Minimum Hot Water Supply Temperature 5°F (3°C) above set point
 Minimum Flow** 0.5 gpm (1.9 lpm)
 Maximum Operating Pressure 150 psi (1034 kPa)
 Temperature Adjustment Range 90 – 160°F (32 – 71°C)
 Listing/Compliance (Valve Only) ASSE 1017, CSA B125

* The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight.


** When tested in accordance with ASSE 1017

Capacity

| Flow Capacity at 50-50 Mixed Ratio | | | | | | | |
|------------------------------------|------|---------------------|----------------------|----------------------|----------------------|----------------------|-----------------------|
| Pressure Differential | | | | | | | |
| Valve | Cv | 5 psi (35 kPa) | 10 psi (69 kPa) | 20 psi (138 kPa) | 30 psi (207 kPa) | 45 psi (310 kPa) | 60 psi (414 kPa) |
| LFLM490 | 3.42 | 7.6 gpm (29 lpm) | 11.0 gpm (42 lpm) | 15.0 gpm (57 lpm) | 19.0 gpm (72 lpm) | 23.0 gpm (87 lpm) | 27.0 gpm (102 lpm) |

Powers product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Powers Technical Service. Powers reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Powers products previously or subsequently sold.

Dimensions



Note:
Dimensions are shown $\pm 1/2$ "
Dimensions in parentheses
are in mm

Ordering Information

L F L M 4 9 0 E S

Valve Order Code

23 gpm (87 lpm)

LFLM490

Finish

Rough Bronze

A

Chrome Plated

C

Piping Inlets/Outlet

Bottom/Top

E

Cabinet Style

Stainless steel, Wall Mount

Q

Painted, Wall Mount

U

View Port

None
Window

Order Code

0
W

Alarm System

None
Aqua Sentry® 2 Alarm

0
4

Option

None
Cold Water Bypass
T/P Gauge on Inlets
C/W Bypass & T/P Gauge on Inlets

0
2
4
6

Temperature Range

Standard 90° – 160°F (32° – 71°C) S

Typical Specification

Cabinet Supply Fixture (CSF) shall be factory assembled and tested and include a stainless steel or painted steel cabinet. CSF shall feature a HydroGuard® LFLM490 Series Master-Tempering Valve with advanced paraffin-based actuation technology. The valves shall be constructed using Lead Free* brass. Lead Free* brass valves shall comply with state codes and standards, where applicable, requiring reduced lead content. CSF shall also include copper piping, ball valve(s) and temperature/pressure gauge for diagnostics. The tempering valve shall have union checkstops, an outlet temperature range of 90 – 160°F (32 – 71°C) (with lockable means), and an approach temperature of 5°F (3°C). Valve shall be ASSE 1017 listed and CSA certified. Minimum flow to ASSE 1017 shall be 0.5 gpm (1.9 lpm).

Valve shall be a Powers model _____. All alternatives must have written approval prior to bidding.

POWERS™

A WATTS Brand

USA: Tel: (800) 669-5430 • Fax: (847) 229-0526 • PowersControls.com
Canada: Tel: (905) 332-4090 • Fax: (905) 332-7068 • PowersControls.ca
Latin America: Tel: (52) 81-1001-8600 • PowersControls.com