

For Commercial & Residential Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Pool & Spa Vacuum Hose



This pool and spa hose utilizes high grade, corrugated ultra-low density polyethylene.

Attributes

Design offers high melting temperature, superior flexibility, crush-proof, and buoyancy.

Applications

- Pool
- Spa
- Vacuum applications



WARNING: Not intended for use with potable water.

Max. Vacuum, Inches of Mercury 29
 Operating Temperature Range -5°F (-21°C) to 150°F (66°C)
 Material Low Density Polyethylene
 Color Blue
 Toxicity Non-Toxic

Packaging

Dispenser spools

Pressure Range

O.D. INCH	I.D. INCH	WALL	WORKING PRESSURE (PSI @ 70°F)
1.58	1-1/4	.165	N/A
1.81	1-1/2	.155	N/A

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: 815 Chestnut St., No. Andover, MA 01845-6098; www.watts.com
Canada: 5435 North Service Rd., Burlington, ONT. L7L 5H7; www.wattscanada.ca

A Watts Water Technologies Company