


**For Commercial & Residential Applications**

Job Name \_\_\_\_\_  
 Job Location \_\_\_\_\_  
 Engineer \_\_\_\_\_  
 Approval \_\_\_\_\_


Contractor \_\_\_\_\_  
 Approval \_\_\_\_\_  
 Contractor's P.O. No. \_\_\_\_\_  
 Representative \_\_\_\_\_

**FloodSafe™**  
**Braided Stainless Steel**  
**Washing Machine Connectors**



**Stainless Steel**

**Features**

- Available in 60" (1524mm) length
- IAPMO Listed 
- Only economical and secure safeguard against catastrophic water damage available on the market
- Patented design
- No mechanical moving parts during normal operation, ensuring years of maintenance free operation
- Does not require electricity, batteries or any other source of power
- Maintenance free
- Installs between the stop valve and the fixture/appliance with the FloodSafe™ device located at the stop valve

**Pressure – Temperature**

Maximum Temperature: 180°F (82°C)  
 Maximum Pressure: 125psi (8.75 bar)

**Note:** A minimum flow rate of 2.5 gallons per minute at the supply connection is required for proper shut off operation. (Typically 30 psi supply pressure meets this requirement.) Performance is accurate to the 80psi Maximum system pressure as required by national plumbing codes.

MODEL	✓ TO SUBMIT	DESCRIPTION	DIMENSIONS		MATERIAL
			A		
			<i>in.</i>	<i>mm.</i>	
FS-5560WMSS		3/4" x 3/4"	60	1524	Stainless Steel

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



**USA:** 815 Chestnut St., No. Andover, MA 01845-6098; [www.watts.com](http://www.watts.com)  
**Canada:** 5435 North Service Rd., Burlington, ONT. L7L 5H7; [www.wattscanada.ca](http://www.wattscanada.ca)