

For Commercial & Residential Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____



Approval _____

Representative _____

Quick'N Easy®

Braided Stainless Steel Dishwasher Connectors

Features

- Available in 48", 60" and 72"
(1219, 1524 and 1829mm) lengths
- NSF & IAPMO Listed  

Pressure – Temperature

Maximum Temperature: 180°F (82°C)

Maximum Pressure: 125psi (8.75 bar)



Stainless Steel

MODEL	✓ TO SUBMIT	DESCRIPTION	DIMENSIONS		MATERIAL
			A		
			<i>in.</i>	<i>mm.</i>	
454 8DWSS		3/8" x 3/8"	48	1219	Stainless Steel
456 0DWSS		3/8" x 3/8"	60	1524	Stainless Steel
456 0DWA		3/8" x 3/8" male adapter	60	1524	Stainless Steel
457 2DWSS		3/8" x 3/8"	72	1829	Stainless Steel
457 2DWA		3/8" x 3/8" male adapter	72	1829	Stainless Steel

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

