




FD-1100-L
Tag: _____

Floor Drain with Square Stainless Steel Strainer

SPECIFICATION: Watts Drainage FD-1100-L epoxy coated cast iron floor drain with anchor flange, reversible clamping collar with primary and secondary weepholes, adjustable heavy duty square heel proof stainless steel strainer, and no hub (standard) outlet.



Str. Dia.	Min.	Max.	Load Rating	Free Area Sq. In.
5"x5"(127x127)	1-1/2"(38)	2-5/16"(59)	*XHD	9
6"x6"(152x152)	1-1/2"(38)	2-5/16"(59)	*XHD	12
8"x8"(203x203)	1-1/2"(38)	2-3/4"(70)	*XHD	26

* The load classifications are in accordance with the American National Standards ASME A112.2.1.1M ASME Ratings are as follows:
XHD - Safe Live Load 7500-10000 lbs.(3375-4500kg)
The above categories are given as a guide only. Please consult factory.

	Std.	P	T	X	60/61
Pipe Size	No Hub	Push On	Female Thread	Inside Caulk	PVC/ABS
2"(51)	3-5/8"(92)	4-1/4"(108)	4-1/4"(108)	4-1/2"(114)	4"(102)
3"(76)	3-5/8"(92)	4-1/4"(108)	4-1/4"(108)	4-1/2"(114)	4"(102)
4"(102)	3-5/8"(92)	4-1/4"(108)	4-1/4"(108)	4-1/2"(114)	4"(102)
6"(152)	3-1/2"(89)				

Components	
B3	B3-XYC
L-3	FC-1
Pipe Sizing (Select One)	
Suffix	Description
2	2"(51) Pipe Size <input type="checkbox"/>
3	3"(76) Pipe Size <input type="checkbox"/>
4	4"(102) Pipe Size <input type="checkbox"/>
6	6"(152) Pipe Size (NH Only) <input type="checkbox"/>
Outlet Type (Select One)	
Suffix	Description
NH	No Hub (MJ) <input type="checkbox"/>
P	Push On <input type="checkbox"/>
T	Threaded Outlet <input type="checkbox"/>
X	Inside Caulk <input type="checkbox"/>
Strainer (Select One)	
Suffix	Description
L5	5"x5" Stainless Steel <input type="checkbox"/>
L6	6"x6" Stainless Steel <input type="checkbox"/>
L8	8"x8" Stainless Steel <input type="checkbox"/>
Options (Select One or More)	
Suffix	Description
-5	Sediment Bucket <input type="checkbox"/>
-6	Vandal Proof <input type="checkbox"/>
-7	Trap Primer Tapping <input type="checkbox"/>
-8	Backwater Valve (2,3,4" Only) <input type="checkbox"/>
-13	Galvanized Body <input type="checkbox"/>
-15	Strainer Extension (DD-50) <input type="checkbox"/>
-28	304SS Body and Collar <input type="checkbox"/>
F4-50	4" Round Cast Iron Funnel <input type="checkbox"/>
F4-1	4" Round Nickel Bronze Funnel <input type="checkbox"/>
F4-3	4" Round SS Funnel <input type="checkbox"/>
F6-1	6" Round Nickel Bronze Funnel <input type="checkbox"/>
G-50	4x9" Oval Cast Iron Funnel <input type="checkbox"/>
G-1	4x9" Oval Nickel Bronze Funnel <input type="checkbox"/>
G-3	4x9" Oval SS Funnel <input type="checkbox"/>
-SO	Side Outlet <input type="checkbox"/>
-US	Buy American Compliant <input type="checkbox"/>
Optional Body Material	
Suffix	Description
-60	PVC Body w/Socket Outlet <input type="checkbox"/>
-61	ABS Body w/Socket Outlet <input type="checkbox"/>

Job Name _____ Contractor _____

Job Location _____ Contractor's P.O. No. _____

Engineer _____ Representative _____

WATTS Drainage reserves the right to modify or change product design or construction without prior notice and without incurring any obligation to make similar changes and modifications to products previously or subsequently sold. See your WATTS Drainage representative for any clarification. Dimensions are subject to manufacturing tolerances.



Specification Drainage Products

USA: 100 Watts Road, Spindale, NC, 28160-2298; TEL: 828-288-2179 TOLL-FREE: 1-800-338-2581 www.watts.com