




FD-200-M

Tag: _____

Floor Drain with Square Heavy Duty Strainer

SPECIFICATION: Watts Drainage FD-200-M on-grade epoxy coated cast iron floor drain with anchor flange, weepholes, adjustable square nickel bronze strainer, and no hub (standard) outlet.



Pipe Sizing (Select One)	
Suffix	Description
2	2" (51) Pipe Size <input type="checkbox"/>
3	3" (76) Pipe Size <input type="checkbox"/>
4	4" (102) Pipe Size <input type="checkbox"/>

Outlet Type (Select One)	
Suffix	Description
NH	No Hub (MJ) <input type="checkbox"/>
P	Push On <input type="checkbox"/>

Strainer (Select One)	
Suffix	Description
M5	5"x5" Nickel Bronze <input type="checkbox"/>
M6	6"x6" Nickel Bronze <input type="checkbox"/>
M8	8"x8" Nickel Bronze <input type="checkbox"/>

Options (Select One)	
Suffix	Description
-5	Sediment Bucket <input type="checkbox"/>
-6	Vandal Proof <input type="checkbox"/>
-7	Trap Primer Tapping <input type="checkbox"/>
-8	Backwater Valve <input type="checkbox"/>
-9	Hinged Grate <input type="checkbox"/>
	(For 6", 8" Strainer Only)
-13	Galvanized Body <input type="checkbox"/>
-15	Strainer Extension (DD-50) <input type="checkbox"/>
-F4-50	4" Round Cast Iron Funnel <input type="checkbox"/>
-F4-1	4" Round Nickel Bronze Funnel <input type="checkbox"/>
-F6-1	6" Round Nickel Bronze Funnel <input type="checkbox"/>
-G-50	4x9" Oval Cast Iron Funnel <input type="checkbox"/>
-G-1	4x9" Oval Nickel Bronze Funnel <input type="checkbox"/>
-US	Buy American Compliant <input type="checkbox"/>

Optional Body Material	
Suffix	Description
-60	PVC Body w/Socket Outlet <input type="checkbox"/>
-61	ABS Body w/Socket Outlet <input type="checkbox"/>

Str. Dia.	Min.	Max.	Load Rating	Free Area Sq. In.
5"x5" (127x127)	7/16" (11)	2 5/16" (59)	*MD	9
6"x6" (152x152)	5/8" (16)	2 5/16" (59)	*MD	12
8"x8" (203x203)	3/4" (19)	2 3/4" (70)	*MD	26

Pipe Size	NH(MJ) No Hub	P Push On	60/61 PVC/ABS
2"	4 1/2" (114)	5 1/2" (140)	4" (102)
3"	4 1/2" (114)	5 1/2" (140)	4" (102)
4"	4 3/4" (121)	5 1/2" (140)	4" (102)

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product

NOTICE

The load classifications are in accordance with the American National Standards ASME A112.21.1M ASME Ratings are as follows:
 HD - Safe Live Load 5000-7499 lbs.(2250-3375 kg)
 The above categories are given as a guide only. Please consult factory.

Load Rating
*MD

Job Name _____
 Job Location _____
 Engineer _____

Contractor _____
 Contractor's P.O. No. _____
 Representative _____

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

USA: Tel: (800) 338-2581 • Fax: (828) 248-3929 • Watts.com
Canada: Tel: (905) 332-4090 • Fax: (905) 332-7068 • Watts.ca
Latin America: Tel: (52) 81-1001-8600 • Fax: (52) 81-8000-7091 • Watts.com

