

For Commercial & Residential Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

Washer Hose

Our Braided Vinyl Tubing is manufactured from Polyvinyl Chloride braided with Polyester.

Attributes

- Smooth, dense bore maximizes flow and reduces sediment buildup
- Has four times the working pressure of single wall PVC

Applications

- Chemical transfers
- Hydraulic lines
- Pneumatic lines
- Coolant lines
- Vacuum lines

⚠ WARNING

Not intended for use with potable water.

Resistant to

Acids, alkalis, variety of chemical, gases and liquids

Operating Temperature Range -40°F (-40°C) to
125°F (52°F)

Material Polyester Reinforced PVC

Color Black

Hardness Durometer 83+/-3 Shore A

Toxicity Non-Toxic FDA compliant
Material

Packaging

Coils, dispenser boxes, dispenser spools

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.



Pressure Range

O.D. INCH	I.D. INCH	WALL	WORKING PRESSURE (PSI @ 70°F)
1	5/8	1/8	200
1-1/8	3/4	1/8	175
1-1/4	7/8	1/8	125
1-3/8	1	1/8	75

NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

USA: T: (978) 689-6066 • F: (978) 975-8350 • Watts.com

Canada: T: (905) 332-4090 • F: (905) 332-7068 • Watts.ca

Latin America: T: (52) 81-1001-8600 • Watts.com