

Advancing Technology for Fire Protection



LFAFBV-FP

Lead Free*
Slow-close ball valve

Reversible
Supervisory
Switch Box
for easy wiring
access



**NFPA 13-compliant
isolation valves
with integrated
supervisory switches**

Gear-operated Ball Valve

- 1", 1¹/₄", 1¹/₂" & 2" diameter, full-port, gear-operated ball valve for fire-suppression system isolation
- Slow-closure rate effectively prevents water hammer and complies with NFPA 13 (6.7.1.2)
- Threaded and grooved end connection options
- Reversible supervisory switch box simplifies electrical wiring access
- UL/FM rated to 400psi to accommodate higher-pressure applications
- Contains two pre-wired single-pole, double-throw, position-indicating supervisory switches
- NEMA 4-rated for indoor and outdoor use



*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.



A Watts Water Technologies Company

USA: Backflow Tel: (978) 689-6066 • Fax: (978) 975-8350 • AmesFireWater.com
USA: Control Valves Tel: (713) 943-0688 • Fax: (713) 944-9445 • AmesFireWater.com
Canada: Tel: (905) 332-4090 • Fax: (905) 332-7068 • AmesFireWater.ca
Latin America: Tel: (52) 81-1001-8600 • Fax: (52) 81-8000-7091 • AmesFireWater.com