

# Silent Check Valve Selector

BODY/MATERIAL	END CONN.	TYPE	SIZE	MODEL NO.	ANSI CLASS	MAXIMUM COLD WATER WORKING PRESSURE @100°F														
						0	100	200	500	1000	2000	3500	5000	6000						
CAST IRON	SCREWED	CENTER GUIDED	¼-2	303AT	N/A	█														
	COM. WAFER	CENTER GUIDED	1-½-6	91AT	N/A	█														
	COM. WAFER	CENTER GUIDED	1-½-6	91AT (CI/SS)	N/A	█														
	COM. WAFER	CENTER GUIDED	8-12	92AT	N/A	█														
	COM. WAFER	CENTER GUIDED	8-10	93AT	N/A	█														
	FULL WAFER	CENTER GUIDED	1-10	101MAT	125	█														
	FULL WAFER	CENTER GUIDED	1-10	103MAT	250	█														
	GLOBE FLANGE	CENTER GUIDED	2-12	105MAT	125	█														
	GLOBE FLANGE	CENTER GUIDED	14-30	105MAT	125	█														
	GLOBE FLANGE	CENTER GUIDED	2-12	107MAT	250	█														
	WAFER	CENTER GUIDED	14-54	71AHH	125	█														
CARBON STEEL	FULL WAFER	CENTER GUIDED	1-10	101MDT	150	█														
	FULL WAFER	CENTER GUIDED	1-10	103MDT	300	█														
	FULL WAFER	CENTER GUIDED	1-6	131DT	600	█														
	GLOBE FLANGE	CENTER GUIDED	2-30	105MDT	150	█														
	GLOBE FLANGE	CENTER GUIDED	2-24	109MDT	300	█														
	GLOBE FLANGE	CENTER GUIDED	2-10	113DT	600	█														
	GLOBE FLANGE	CENTER GUIDED	2-24	117DT	1500	█														
STAINLESS STEEL	SCREWED	CENTER GUIDED	¼-2	303HT	N/A	█														
	FULL WAFER	CENTER GUIDED	1-10	101MHT	150	█														
	FULL WAFER	CENTER GUIDED	1-10	103MHT	300	█														
	FULL WAFER	CENTER GUIDED	1-6	131HT	600	█														
	GLOBE FLANGE	CENTER GUIDED	2-30	105MHT	150	█														
	GLOBE FLANGE	CENTER GUIDED	2-24	109MHT	300	█														
	GLOBE FLANGE	CENTER GUIDED	2-10	113HT	600	█														
	GLOBE FLANGE	CENTER GUIDED	2-24	117HT	1500	█														
BRONZE	BRONZE	CENTER GUIDED	¼-2	303BP	N/A	█														
	FULL WAFER	CENTER GUIDED	1-10	101MBP	150	█														
	FULL WAFER	CENTER GUIDED	1-16	103MBP	300	█														
	GLOBE FLANGE	CENTER GUIDED	2-30	105MBP	150	█														
	GLOBE FLANGE	CENTER GUIDED	2-20	109MBP	300	█														

Mueller Steam Specialty product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Mueller Steam Specialty Technical Service. Mueller Steam Specialty reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Mueller Steam Specialty products previously or subsequently sold.



A Watts Water Technologies Company

USA: Tel: (800) 334-6259 • Fax: (800) 421-6772 • MuellerSteam.com

Latin America: Tel: (52) 81-1001-8600 • Fax: (52) 81-8000-7091 • MuellerSteam.com